

	Item	Spec.		
E L E C T R I C A L	Frequency Range	1600MHz ~ 1750MHz	BW : 150MHz	
	Insertion Loss (Max.)	1.0dB	-	
	VSWR (Max.)	1.5 : 1	-	
	Ripple (Max.)	1610MHz ~ 1750MHz : 0.3dB		
		1600MHz ~ 1605MHz : 0.4dB		
		1605MHz ~ 1610MHz : 0.3dB		-
	Upper Stop Band Rejection	1900MHz ~ 2050MHz : 25dB		Min.
		2200MHz ~ 2400MHz : 30dB		
	Ultimate Rejection	3000MHz ~ 6000MHz : 60dB		Min.
		DC ~ 1300MHz : 60dB		
	GPS Band Rejection	1575MHz ± 2MHz : 50dB		Min.
		1585MHz : 20dB		
	Group Delay	1615MHz ~ 1750MHz : 2ns max.		-
		1600MHz ~ 1615MHz : TBDns		-
Impedance	50Ω ± 5.0		-	
Average Power	10W		-	
IN/OUT Port (Connector Type)	SMA Type Female		-	
E N V I R O N M E N T	Relative Humidity	0%~95%	-	
	Operating Temp	-40℃~+85℃	-	
	Vib.Amplitude	10 ~ 150Hz	-	
	Acceleration	2G	-	
	Sweep	0.1Octaves/Min.	-	
	Recycle	1 return	-	
	Direction	X, Y, Z	-	
Dimension(W X D X H)		90 X 48 X 34		