

	Item	Spec.	
E L E C T R I C A L	Frequency Range	1630MHz ~ 1750MHz	BW : 130MHz
	Insertion Loss (Max.)	1.0dB	-
	VSWR (Max.)	1.5 : 1	-
	Ripple (Max.)	0.4dB	-
	Upper Stop Band Rejection	1900MHz ~ 2050MHz : 25dB	Min.
		2200MHz ~ 2400MHz : 30dB	
	Ultimate Rejection	3000MHz ~ 6000MHz : 60dB	Min.
		DC ~ 1300MHz : 60dB	
	GPS Band Rejection	1575MHz ± 2MHz : 50dB	Min.
		1585MHz : 30dB	
	Group Delay	1630MHz ~ 1750MHz : 2ns	-
	Impedance	50Ω ± 5.0	-
Average Power	4W	-	
IN/OUT Port (Connector Type)	SMA Type Female	-	
E N V I R O N M E N T	Relative Humidity	0%~95%	-
	Operating Temp	-40℃~+85℃	-
	Vib.Amplitude	10 ~ 150Hz	-
	Acceleration	2G	-
	Sweep	0.1Octaves/Min.	-
	Recycle	1 return	-
	Direction	X, Y, Z	-
Dimension(W X D X H)		57 X 40 X 34	